


ALT-2000



WWW.SASTESTERS.COM

Ph: +972-9-7603895

Fax: +972-9-7604849

E-Mail: Info@SASTESTERS.COM

Specifications		
Tester Load	<input type="checkbox"/> Load Capacity 2000N (450.0lbf) <input type="checkbox"/> Load Resolution 0.05N (0.011lbf) <input type="checkbox"/> Load Accuracy $\pm 0.1N$ ($\pm 0.022lbf$) <input type="checkbox"/> Continuous digital display or Force/Load height graphical analysis tools and display <input type="checkbox"/> Safe overload to 150% of FS (compression and tension overload protection at 100% of FS load)	
Tester Stroke	<input type="checkbox"/> Stroke 500mm (20") Standard <input type="checkbox"/> Resolution: 0.25micron (0.00001") for High Resolution Models, - Standard <input type="checkbox"/> Accuracy: better than 0.01mm (0.0004") – Available with independent Calibration for High Resolution Models <input type="checkbox"/> Absolute display of load height above a user defined fixed reference.	
Tester Platten Diameter	<input type="checkbox"/> 80mm (3.15")	
System Computer	<input type="checkbox"/> Intel dual Core (minimum) processor <input type="checkbox"/> Built-In PC. <input type="checkbox"/> Fully Microsoft Windows XP and Win7 and Win 10 compatible	Display 17" Touch Screen Built – In Monitor.
Software Languages	<input type="checkbox"/> English, German, French and Spanish	
Software Features	<input type="checkbox"/> Programmable for automated testing, Includes frelength, initial tension and spring rate results. Solid Height detection included. <input type="checkbox"/> Over 200 programmable test points available <input type="checkbox"/> Full reporting and printing capability available. <input type="checkbox"/> On-Line and off-line SPC control charts and Cpk capability testing available. <input type="checkbox"/> Smart self calibration routines	
Units	<input type="checkbox"/> N, kgf, gf, ozf, lbf – mm, inches	
Tester Crosshead Test speeds	<input type="checkbox"/> 1.5mm/s – 125mm/s (3.5"/min – 294"/min)	
	<input type="checkbox"/>	
TurnTable	<input type="checkbox"/> 12 Turntable Stations Including: <input type="checkbox"/> Loading Station <input type="checkbox"/> 3 Setting Stations <input type="checkbox"/> 1 Test Station <input type="checkbox"/> 1 unloading/ Sorter Station	
Setting	<input type="checkbox"/> Pneumatic Setting <input type="checkbox"/> 5000N Maximum Setting Capacity <input type="checkbox"/> Can be mechanically divided into 3 setting stations. (for 3 setting stations, each station capacity up to 1666N) <input type="checkbox"/> 200mm setting stroke <input type="checkbox"/> Number of setting actions—programmable <input type="checkbox"/> Mechanical lower stopper to setup setting height if required <input type="checkbox"/> Mechanical upper stop to reduce set times for different spring sizes	
Sorting	<input type="checkbox"/> Programmable 3 way sorting for one test parameter <input type="checkbox"/> Programmable 2 way sorting for multiple test parameters	
Loading	<input type="checkbox"/> Manual loading <input type="checkbox"/> Optional automatic loading mechanism available that can be connected to bowlfeeders	
Power	<input type="checkbox"/> 110V~220V AC 4.5A (Maximum)	
Testing Speeds / Part Throughput	<input type="checkbox"/> Depends on part frelength, required test stroke, number of required test parameters <input type="checkbox"/> For example: 1 test parameter with a 10mm test stroke, ---Approximately 2500 springs per hour can be tested	