


ALT-5000



WWW.SASTESTERS.COM

Ph: +972-9-7603895

Fax: +972-9-7604849

E-Mail: Info@SASTESTERS.COM

Specifications

Tester Load	<ul style="list-style-type: none"> <input type="checkbox"/> Load Capacity 5000N (1121.0lbf) <input type="checkbox"/> Load Resolution 0.10N (0.0224lbf) <input type="checkbox"/> Load Accuracy $\pm 0.125N$ ($\pm 0.0281\text{lbf}$) at 0.5% of Range <input type="checkbox"/> Continuous digital display or Force/Load height graphical analysis tools and display <input type="checkbox"/> Safe overload to 150% of FS (compression and tension overload protection at 100% of FS load) 	
Tester Stroke	<ul style="list-style-type: none"> <input type="checkbox"/> Stroke 500mm (20") Standard <input type="checkbox"/> Resolution: 0.25micron (0.00001") for High Resolution Models, - Standard <input type="checkbox"/> Accuracy: better than 0.01mm (0.0004") – Available with independent Calibration for High Resolution Models <input type="checkbox"/> Absolute display of load height above a user defined fixed reference. 	
Tester Platten Diameter	<ul style="list-style-type: none"> <input type="checkbox"/> 80mm (3.15") 	
System Computer	<ul style="list-style-type: none"> <input type="checkbox"/> Intel dual Core (minimum) processor <input type="checkbox"/> Built-In PC. <input type="checkbox"/> Fully Microsoft Windows XP and Win7 and Win 10 compatible 	Display 17" Touch Screen Built – In Monitor.
Software Languages	<ul style="list-style-type: none"> <input type="checkbox"/> English, German, French and Spanish 	
Software Features	<ul style="list-style-type: none"> <input type="checkbox"/> Programmable for automated testing, Includes frelength, initial tension and spring rate results. Solid Height detection included. <input type="checkbox"/> Over 200 programmable test points available <input type="checkbox"/> Full reporting and printing capability available. <input type="checkbox"/> On-Line and off-line SPC control charts and Cpk capability testing available. <input type="checkbox"/> Smart self calibration routines 	
Units	<ul style="list-style-type: none"> <input type="checkbox"/> N, kgf, gf, ozf, lbf – mm, inches 	
Tester Crosshead Test speeds	<ul style="list-style-type: none"> <input type="checkbox"/> 1.5mm/s – 125mm/s (3.5"/min – 294"/min) 	
Turn Table	<ul style="list-style-type: none"> <input type="checkbox"/> 12 Turntable Stations Including: <input type="checkbox"/> Loading Station <input type="checkbox"/> 3 Setting Stations <input type="checkbox"/> 1 Test Station <input type="checkbox"/> 1 unloading/ Sorter Station 	
Setting	<ul style="list-style-type: none"> <input type="checkbox"/> Pneumatic Setting <input type="checkbox"/> 5000N Maximum Setting Capacity Standard <input type="checkbox"/> 10000N Setting Capacity Optional <input type="checkbox"/> Can be mechanically divided into 3 setting stations. (for 3 setting stations, each station capacity up to 1666N standard or 3333N Optional) <input type="checkbox"/> 200mm setting stroke <input type="checkbox"/> Number of setting actions—programmable <input type="checkbox"/> Mechanical lower stopper to setup setting height if required <input type="checkbox"/> Mechanical upper stop to reduce set times for different spring sizes 	
Sorting Loading	<ul style="list-style-type: none"> <input type="checkbox"/> Programmable 3 way sorting for one test parameter <input type="checkbox"/> Programmable 2 way sorting for multiple test parameters 	
Power	<ul style="list-style-type: none"> <input type="checkbox"/> Manual loading <input type="checkbox"/> Optional automatic loading mechanism available that can be connected to bowlfeeders 	
Testing Speeds / Part Throughput	<ul style="list-style-type: none"> <input type="checkbox"/> 110V~220V AC 4.5A (Maximum) 	
Testing Speeds / Part Throughput	<ul style="list-style-type: none"> <input type="checkbox"/> Depends on part frelength, required test stroke, number of required test parameters <input type="checkbox"/> For example: 1 test parameter with a 10mm test stroke, ---Approximately 2500 springs per hour can be tested 	