

CT-10PC



CT-10PC Specifications

Load

- Load Capacity 10N (2.25lbf)
- Load Resolution 0.0002N (000045lbf)
- Load Accuracy per ISO 7500 /1 Class 0.5 (0.5% of load, between 0.5% capacity up to full capacity)
- Recommended minimum load:0.08N (0.018lbf)
- Continuous digital display or Force/Load height graphical analysis tools and display
- Safe overload to 150% of FS (compression and tension overload protection at 100% of FS load)

Stroke

- 500mm (20") standard
- 1000mm(40") Optional
- Resolution: 0.00025mm (0.0000098") for 500mm and 1000mm stroke Model
- Accuracy: ± 0.01 mm (± 0.00039 ") for 500 stroke Model, Accuracy: better than 0.005mm– Available with independent Calibration for HS Model

Platten

Diameter

Free Length

Spring rate

Initial tension

Computer

Languages

Software Features

Units

Test speeds

Power

- 80mm (3.15")
- Automatically determined.
- Conductive contact Freelength module optional
- Automatic or manual determination of spring rate (linear analysis), option for characterization of non-linear rates (e.g. conical springs)
- Automatic detection of tension spring initial tension.
- Intel dual Core (minimum) processor
- Built-In PC.
- Fully Microsoft Win10 and Win11 compatible
- English, German, French, Russian, and Turkish
- Programmable for automated testing, Includes freelength, initial tension and spring rate results. Solid Height detection included.
- Full reporting and printing capability available.
- On-Line and off-line SPC control charts and Cpk capability testing available.
- Design and reverse engineering algorithms
- Smart self calibration routines
- Fatigue module
- N, kgf, gf, ozf, lbf – mm, inches
- 0.1mm/s – 125mm/s (0.236"/min-295.3"/min)
- 12 distinct speed settings
- 110V~220V AC 4.5A (Maximum)

Display 22"
Touch Screen
Built – In
Monitor.



WWW.SASTESTERS.COM

Ph: +972-9-7603895

Fax: +972-9-7604849

E-Mail: Info@SASTESTERS.COM