


CFT Series Fatigue Testers

Large Stroke Life Cycle Testing

- **6 Station PC Models-** independent measuring and recording of load on each station.
- **Up To 2000mm Stroke**
- **Max Testing Speed of 130mm/sec**



Specifications

CFT21000-6

Number of test stations	6
Number of Test heads	1
Maximum total load N (lbf)	20000 (4500)
Maximum load per test station N (lbf)	3333(750)
Maximum compression spring OD mm (in)	80 (3.3)
Maximum adjustable compression spring free length mm (in)	2000 (80)
Maximum speed (mm/sec)*	133
Maximum stroke mm (in)	1500 (60)
Fatigue cycle count and stop when count reached	√
Programmable stop when one spring, all springs fail, after time period	√
Programs per spring type stored for easy recall and setup	√
Fatigue loads recorded per cycle and gap cycles	√
Load recorded for relaxation evaluation	√
Optional tension spring attachments per spring type	√
Intel Dual core 2 PC, 23" LCD monitor, Windows 10 or Win11	√
L x B x H mm (in), excluding control cabinet	100x100x270 25x25x106
Weight kg (lb)	800 (1760)
Supply	380V 3PH max 32A

*-Load and Stroke derating applies



WWW.SASTESTERS.COM

Ph: +972-9-7603895

Fax: +972-9-7604849

E-Mail: Info@SASTESTERS.COM

Specifications may change without notice