

CTM-100



Specifications

Load

- ☐ Load Capacity 100N (22.5lbf)
- ☐ Load Resolution 0.002N (0.00045lbf)
- ☐ Load Accuracy per ISO 7500 /1 Class 0.5 (0.5% of load, between 0.5% capacity up to full capacity)
- ☐ Continuous digital display or Force/Load height graphical analysis tools and display
- ☐ Safe overload to 150% of FS (compression and tension overload protection at 100% of FS load)

Stroke

- ☐ Stroke 200mm (8") Standard
- ☐ Resolution: 0.003mm (0.0002") for 200 stroke, - Standard Model
- ☐ Accuracy: $\pm 0.02\text{mm}$ ($\pm 0.0008"$) for 200 stroke on standard model , Absolute display of load height above a user defined fixed reference.

Platten

Diameter

- ☐ 55mm (2.2")

Free Length

- ☐ Automatically determined.

Spring rate

- ☐ Automatic or manual determination of spring rate (linear analysis), option for characterization of non-linear rates (e.g. conical springs)

Initial tension

- ☐ Automatic detection of tension spring initial tension.

Computer

- ☐ Pocket PC, Intel Atom
- ☐ USB internal connection to PC for control and data transfer
- ☐ Fully Microsoft Windows 10

Display 7"
TouchScreen.

Languages

- ☐ English, German, Russian, Chinese

Software

Features

- ☐ Programmable for automated testing, Includes frelength, initial tension and spring rate results.
- ☐ Full reporting and printing capability available.
- ☐ On-Line and off-line SPC control charts and Cpk capability testing available.
- ☐ Smart self calibration routines

Units

- ☐ N, kgf, gf, ozf, lbf – mm, inches

Test speeds

- ☐ Manual Testing

Power

- ☐ 110V~220V AC 1.5A (Maximum)



WWW.SASTESTERS.COM

Ph: +972-9-7603895

Fax: +972-9-7604849

E-Mail: Info@SASTESTERS.COM