

# CTM-2000



## Specifications

### Load

- Load Capacity 2000N (450lbf)
- Load Resolution 0.04N (0.0090lbf)
- Load Accuracy per ISO 7500 /1 Class 0.5 (0.5% of load, between 0.5% capacity up to full capacity)
- Continuous digital display or Force/Load height graphical analysis tools and display
- Safe overload to 150% of FS (compression and tension overload protection at 100% of FS load)

### Stroke

- Stroke 200mm (8") Standard
- Resolution: 0.003mm (0.0002") for 200 stroke, - Standard Model
- Accuracy:  $\pm 0.02\text{mm}$  ( $\pm 0.0008\text{"}$ ) for 200 stroke on standard model , Absolute display of load height above a user defined fixed reference.

### Platten

- 55mm (2.2")

### Diameter

- Automatically determined.

### Free Length

- Automatic or manual determination of spring rate (linear analysis), option for characterization of non-linear rates (e.g. conical springs)

### Spring rate

- Automatic detection of tension spring initial tension.

### Initial tension

### Computer

- Pocket PC, Intel Atom
- USB internal connection to PC for control and data transfer
- Fully Microsoft Windows 10

Display 7"  
TouchScreen.

### Languages

- English, German, Russian, Chinese

### Software

### Features

- Programmable for automated testing, Includes frelength, initial tension and spring rate results.
- Full reporting and printing capability available.
- On-Line and off-line SPC control charts and Cpk capability testing available.
- Smart self calibration routines

### Units

- N, kgf, gf, ozf, lbf – mm, inches

### Test speeds

- Manual Testing

### Power

- 110V~220V AC 1.5A (Maximum)



[WWW.SASTESTERS.COM](http://WWW.SASTESTERS.COM)

Ph: +972-9-7603895

Fax: +972-9-7604849

E-Mail: [Info@SASTESTERS.COM](mailto:Info@SASTESTERS.COM)